



SELF-PRIMING PUMPS



# ETM

## X · PRO



Pressure regulating knob with anti-tampering device

*Manopola regolazione pressione con dispositivo anti-manomissione*



LW-K 250

### PRO VERSIONS

Pump with 3 integral ceramic pistons. Oil sight glass. Brass pump heads

### VERSIONI PRO

*Pompa con 3 pistoni in ceramica integrale. Visore livello olio. Testate in ottone*



GXR

### X VERSIONS

Comet electrical pump with three axial pistons arranged vertically with pump at the bottom and an all-metal construction without any plastic used for the structural components

### VERSIONI X

*Elettropompa Comet a tre pistoni assiali disposta in verticale con pompa in basso e costruzione interamente in metallo, senza materiale plastico nei componenti strutturali*



**GENERAL FEATURES · CARATTERISTICHE GENERALI**

- Easy to transport thanks to a practical top grip and anti-vibration supports
- Induction 2-pole motor (2800 rpm) on ETM 150 X model
- 4-pole motor (1400 rpm) on ETM 150 PRO model
- Built-in professional unloader valve with ejector
- EASY START device
- Total Stop system
- Rotary switch
- Motor thermal protection
- Semplicità di trasporto mediante confortevole impugnatura superiore ed appoggio su supporti antivibranti
- Motore a 2 poli a induzione (2800 giri/min) per modello ETM 150 X
- Motore a 4 poli (1400 giri/min) per modello ETM 150 PRO
- Valvola di regolazione professionale integrata con eiettore
- Dispositivo EASY START
- Dispositivo Total Stop
- Interruttore rotativo
- Protezione termica del motore
- Uso semiprofessionale gravoso (uso professionale per ETM 150 PRO)

**TECHNICAL FEATURES · CARATTERISTICHE TECNICHE**

CODE CODICE	MODELS MODELLI	PUMP POMPA	Ph V Hz			MAX bar MPa		WORK bar MPa		I/h		HP kW		kW		kg		(L x W x H) cm	
			Ph	V	Hz	bar	MPa	bar	MPa	I/h	HP	kW	kW	kg	(L x W x H) cm				
36016-00028	ETM 150 X	GXR	1	230	50	150	15	30 ÷ 135	3 ÷ 13,5	280 ÷ 600	3,0	2,2	2,9	25	26 x 47 x 37				
36016-00027	ETM 150 PRO	LW-K 250	1	230	50	150	15	30 ÷ 135	3 ÷ 13,5	280 ÷ 600	3,0	2,2	2,9	35	26 x 47 x 37				

**STANDARD EQUIPMENT · DOTAZIONE STANDARD**

<p>X</p>  <p>GC 201 gun with protection Pistola GC 201 con protezione</p>	<p>PRO</p>  <p>GC 251 gun with protection Pistola GC 251 con protezione</p>	<p>X</p>  <p>Lance with adjustable jet, with nozzle Lancia getto regolabile con ugello</p>
<p>PRO</p>  <p>Bent lance with detergent head, without nozzle Lancia angolata con testina detergente, senza ugello</p>	<p>PRO</p>  <p>15° spray nozzle, 1/4" MEG connection Ugello con getto a lama 15° attacco 1/4" MEG</p>	<p>X   PRO</p>  <p>R1 1/4" 10 m rubber delivery hose kit Kit tubo mandata in gomma 10 m R1 1/4"</p>